

Exxsol™ Hexane

Dearomatized Fluid

Properties	Minimum	Maximum	Unit	Test Method
Appearance	Bright & Clear		-	ASTM D4176(mod) ECIM 1001
Aromatic Content		0.01	vol%	ECIM 2001
Color, Saybolt	30		-	ASTM D6045 ECIM 1002
n-Hexane	45	65	vol%	ECIM 2005

Distillation	Minimum	Maximum	Unit	Test Method
Distillation - Initial Boiling Point (IBP)	52.8		°C	ASTM D5399(mod) ECIM 2008
Distillation - Dry Point (DP)		94.6	°C	ASTM D5399(mod) ECIM 2008

Additional Information

Imperial Oil or ExxonMobil's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing date, periodic testing and/or most recent product restock. Imperial Oil reserves the right to use other equivalent test methods in certifying this product.

Specification Region

North America

For additional technical, sales and order assistance, please contact your sales representative or call 1 (778) 753-7466.

© 2019 Imperial Oil. The Imperial logo is a trademark of Imperial Oil Limited. Imperial Oil, licensee. All other product or service names used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise. Imperial Oil, licensee. This document may not be distributed, displayed, copied or altered without Imperial Oil's prior written authorization. To the extent Imperial Oil authorizes distributing, displaying or copying this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. Imperial Oil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with

Sales Specification
Exxsol™ Hexane
Dearomatized Fluid

any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-Imperial Oil product or process, and we expressly disclaim any contrary implication. The term "ExxonMobil" is used for convenience and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation or any affiliate of such entities either directly or indirectly stewarded.